



- NOTES:
1. Rating:300V 15A;
 2. Insulation Withstands Voltage: AC2000V/MIN
 3. Insulation Resistance: 500MΩ or more at DC500V
 4. Using Temperature Range: -40°C~+105°C
 5. Screw Torque Viaue:0.4N.m
 6. Suitable Electric Wire: 28~12AWG
 7. "★" is the important dimension.

REV	CONTENT	CHK	DATE
V0.0	CONTENT	SK	2014/09/11

Total Pitch Tolerances		Nominal dimension range																								
in mm		in mm																								
over	to	0	30	53	70	90	115	150	250	350	500	0	30	53	70	90	115	150	200	250	0	10	all	0	100	150
±0.18?	±0.20	±0.25	±0.3	±0.35?	±0.4	±0.60	±0.70?	±0.85	±0.20	±0.25	±0.30	±0.35	±0.4	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.3	0.5	

5	CLAMP	ZK400C0001	P	BRONZE	Ni Plated
4	BLOCK	ZBXC0001	P	BRASS	Ni Plated
3	SCREW	ZBST0023	P+2	STEEL	M2.5/Zn Plated
2	HOUSING	ZK400A4XXXX	1	PA66	UL94V-0
1	COVER	ZK400A5XXXX	1	PA66	UL94V-0

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	SK	DATE	2014/09/11	SIZE	A4
CHK	DATE	SCALE	2.5:1	UNITS	mm
APP.	DATE	SCALE	2.5:1	SHEET/OF	1/1



NINGBO ZHONGBO PHOTOVOLTAIC TECHNOLOGY CO., LTD

DWGNO: ZB-02-ZBK400RMXXPPXS